

















































TECHNICAL CHARACTERISTICS





























bearings). Extruded aluminum rail.

• Re-adjustable square for long lasting precision.



• Heavy duty water pump and (2) jet nozzles provide superior blade cooling.

• Pivoting blade guard remains parallel with tile to ensure maximum cutting depth.

• Floating blade guard remains in contact with tile to provide extra safety during operation. • Equipped with: diamond disc Ø 350 mm (14") for porcelain tiles, wheels kit for easy transport,

• Telescopic legs provided with safety device to prevent collapsing.

pressure device to hold tile, key kit, wrench, manual.



• Sliding motor assembly with cast aluminum housing provided with 4 re-adjustable pulleys (double

2800







- For cutting granite, marble, porcelain, single and double fired, bricks, cement, etc...
- Maximum length of cut 130 cm (51 1/8").
- Maximum thickness of cut: 110 mm (4 1/3") in single pass; 235 mm (9 1/4") in double pass.
- Maximum blade diameter Ø 360 mm (14"); smallest blade diameter Ø 300 mm (12").
- Adjustable cutting depth.
- \bullet Tilting motor assembly for bevel cuts from 0° to $45^{\circ}.$
- Belt driven system optimizes motor torque and cutting capacity. Gear ratio of motor to disc 1,4 \div 1. Drive belt type poly V.
- Cast and extruded aluminum framework.

MODEL SPECIFICATIONS											
Part No.			M	M			•				
420130A P	8050532006560	1	230 V 50 Hz	Single-phase	3 HP/2,2 kW	2800	350 mm 14	" 2000			
420130A 400VP	8050532006584	1	400 V 50 Hz	Three-phase	3 HP / 2,2 kW	2800	350 mm 14	2000			
420130A 60HZP	8050532006591	1	230 V 60 Hz	Single-phase	3 HP/2,2 kW	3360	350 mm 14	2400			
420130A USP	8024648056900	1	110 V 60 Hz	Single-phase	2.2 HP/1.65 kW	3360	350 mm 14	" 2400			

420130A GBP 8050532006553 CUTTING SPECIFICATIONS AND MACHINE DIMENSIONS /WEIGHT

COTING SI CONCATIONS AND MACHINE DIMENSIONS/ WEIGHT											
	Model	+									>
	ZOE 130 ADV	Ø 350 mm 14"	110 mm 4 1/3"	80 mm 3 1/8"	130 cm 51 1/8"	∞	90x90 cm 35 3/8"x35 3/8"	170x70xh 95 cm 67"x27"x h 37"	98 Kg 216 lbs	200x80xh 110cm 78 3/4"x31 1/2"x h 43"	139 Kg 306.4 lbs

Single-phase





110 V 50 Hz



2,2 HP/1,65 kW



350 mm 14"

2000